
TOMBO[™] BRAND

Gaskets for use in buildings





Gaskets for building pipework

CLINSIL[™]-BROWN

■TOMBO[™] No.1995


Inorganic filler is added to inorganic fibers and aramid fibers; then oil-resistant synthetic rubber is added as binder to form brown jointing sheets.

Applications

•Gaskets for flanges of the building pipework except for that for use with steam and high temperature water.

Service range

- Temperature: Lower than 100°C
- Pressure: Less than 2.0MPa (20kgf/cm)
- •In the case of gas sealing, ring shape (FR) gasket in 1.5mm thickness is recommendable.



NAFLON[™] PTFE ENVELOPE GASKET

●TOMBO[™] No.9010-A-5


The core of jointing sheet is covered with a thin film of PTFE. This gasket is suitable for use with fluids that do not allow contamination, corrosive fluids and also suitable for use in sealing stainless steel pipework.

Applications

- Clean water pipework
- Stainless steel pipework for cooling water, etc.
- Electrical insulation gasket (different in inner diameter from that for use in sealing pipework)

Service range

- Temperature: Lower than 100°C
- Pressure: Less than 2.0MPa (20kgf/cm)
 - The above pressure indicates the use at ambient temperatures. Service pressure becomes lower at high temperatures.




The above diagram shows the cross-sectional view of the gasket.

Selection table of gaskets for building pipework


Fluids	Service conditions		
	Temperature	Pressure	Products (TOMBO [™] No.)
Water (Heated and cold water, Water supply and drainage), Oil	Lower than 100°C	Less than 2.0MPa	1995
Drinking water (Stainless steel pipework)	Lower than 100°C	Less than 2.0MPa	9010-A-5
Water (PVC pipework)	Lower than 100°C	Less than 1.0MPa	9013 (NAFLON in contact with fluid)
Steam	Lower than 220°C	Less than 2.0MPa	1834-NA-EOS
Electrical insulation gasket	Lower than 200°C	Less than 2.0MPa	1834-NA-EOS+9007-LC
	Lower than 150℃	Less than 1.0MPa	9007-LC
	Lower than 100°C	Less than 2.0MPa	9010 - E (Different in inner diameter from that for general piping)

● The above selection is made only for the building pipework application. Selection criteria are partly different from those for 'TOMBO[™] Brand gaskets' catalog due to difference of application.

Please contact us for service conditions other than those mentioned above.



 The above diagram shows the cross-sectional view of the flanges and pipework.



NA VORTEX[™] GASKET

●TOMBO[™] No.1834-NA-EOS

NA VORTEX GASKETS are spiral wound gaskets that are made of V-shaped and thin stainless steel strips (hoops) and papers (cushioning filler). These gaskets are excellent in sealability for the service range at high temperature and high pressure due to their unique structure. These gaskets are recommendable for use with steam pipework and high temperature water pipework.

Applications

Steam pipework

High temperature water pipework

Service range

- Temperature: Lower than 220°C
- Pressure: Less than 2.0MPa (20kgf/cm)

EBILON[™] GASKET (PTFE Jacketed)

■TOMBO[™] No.9013

These are rubber-molded gaskets with bead-like configuration that makes them sealable at low seating stress. These gaskets have both elasticity of EPDM rubber that is excellent in water resistance and weather resistance and corrosion resistance of NAFLON PTFE.

Applications

Plastic pipework

Clean water and sewage pipework

Service range

- ●Temperature: Lower than 100℃
- Pressure: Less than 2.0MPa (20kgf/cm)

Specification standard

Product name	Specification Standard
CLINSIL [™] -BROWN	JIS F 0602 HJ

Standard dimensions

Product name	Thickness (mm)	Standard dimensions (mm)
TOMBO [™] No.1995 CLINSIL [™] -BROWN	0.8 1.0 1.5 2.0 3.0	1270×1270 1270×3810



•Use these products within the service temperature limit.

- ●Refer to the SDS (Safety Data Sheet) prior to use of these products.
- •Comply with your local regulations in the case of disposal of these products.
- •Refer to the cautions for each product listed in the TOMBO BRAND Gaskets catalog for selection of products.



Head Office

6-1, Hatchobori 1-chome, Chuo-ku, Tokyo 104-8555, Japan International Marketing and Sales Group Phone: 81-3-4413-1132 Fax: 81-3-3552-6108 Web Site: http://www.nichias.co.jp/

Overseas Representative Offices

NICHIAS CORPORATION, QATAR REPRESENTATIVE OFFICE P.O. Box 200138, 7th Floor Pearl Tower, Al Matar Street, Doha, Qatar Phone: +974-4498-7221 Fax: +974-4443-5495

Overseas Sales Companies Indonesia

PT. NICHIAS SUNIJAYA

Panin Life Center, 2nd Floor, Room 205, Jl. Letnan Jenderal S. Parman Kav. 91, Jakarta 11420, Indonesia Phone: +62-21-56956207 Fax: +62-21-56956208/56956209

Malaysia

NICHIAS FGS SDN. BHD. Kuala Lumpur Sales Office Suite A1102, 11th Floor, West Wing, Wisma Consplant 2, No.7, Jalan SS 16/1, 47500 Subang Jaya, Selangor, Malaysia Phone: +60-3-5636-4067 Fax: +60-3-5636-4078

Singapore

NICHIAS SINGAPORE PTE. LTD.

25 International Business Park, #01-15/17 German Centre, Singapore 609916 Phone: +65-6571-0830/0838 Fax: +65-6265-7681 Vietnam

NICHIAS VIETNAM CO., LTD

Room 12-K, 12Floor, Center Building, Hapulico Complex No1 Nguyen Huy Tuong, Thanh Xuan Trung, Thanh Xuan, Hanoi, Vietnam Phone: + 84-4-3791-7194 Fax: + 84-4-3791-6203

Thailand

NICHIAS (THAILAND) CO., LTD. 85 Moo 1, Wellgrow Industrial Estate T. Homsin, A. Bangpakong

Chachoengsao 24180, Thailand Phone: +66-38-570-600 Fax: +66-38-570-601

THAI NICHIAS INTERNATIONAL CO., LTD.

Unit 1107, 11th Floor, AIA Capital Center 89 Ratchadaphisek Road, Dindaeng, Dindaeng, Bangkok 10400 Thailand Phone: +66-2-001-2060 Fax: +66-2-001-2062

China

NICHIAS (SHANGHAI) TRADING CO., LTD. 霓佳斯(上海) 贸易有限公司 2109 Building A, City Center of Shanghai, No.100 Zun Yi Road, Changning District, Shanghai, 200051, P.R.China 中国上海市长宁区遵义路100号虹桥上海城A栋2109室 邮编200051 Phone: +86-21-62361783 Fax: +86-21-62361781

NICHIAS (SHANGHAI) TRADING CO., LTD. Guangzhou Branch

 電佳斯(上海) 贸易有限公司 广州分公司

 17F-G, Gold Sun Building, No.109 Tiyu West Road, Guangzhou,
 Guang Dong Province, 510620, P.R.China
 中国广东省广州市天河区体育西路109号高盛大厦17楼G室 邮编 510620

 Phone: +86-20-3879-1640 Fax: +86-20-3879-1647

NICHIAS (SHANGHAI) AUTOPARTS TRADING CO., LTD. 霓佳斯(上海)汽车零部件贸易有限公司 2108 Building A, City Center of Shanghai, No.100 Zun Yi Road, Changning District, Shanghai, 200051, P.R.China 中国上海市长宁区遵义路100号虹桥上海城A栋2108室 邮编200051 Phone: +86-21-6236-2668 Fax: +86-21-6236-2667

Overseas Construction Companies Malaysia

NICHIAS SOUTHEAST ASIA SDN. BHD.

Suite A1102, 11th Floor, West Wing, Wisma Consplant 2, No. 7, Jalan SS 16/1, 47500 Subang Jaya, Selangor Darul Ehsan, Malaysia. Phone: +60-3-5636-4067 Fax: +60-3-5636-4078 Thailand

THAI-NICHIAS ENGINEERING CO., LTD.

45 Huaypong-Nongbon Road, Huaypong, Muang Rayong, Rayong Province 21150, Thailand Phone: +66-38-682-242 Fax: +66-38-691-156

Overseas Factories

Indonesia PT. NICHIAS ROCKWOOL INDONESIA PT. NICHIAS METALWORKS INDONESIA Malavsia NICHIAS FGS SDN. BHD. NT RUBBER-SEALS SDN. BHD. Vietnam NICHIAS HAIPHONG CO., LTD. China SUZHOU NICHIAS INDUSTRIAL PRODUCTS CO., LTD. (苏州霓佳斯工业制品有限公司) SUZHOU NICHIAS SEAL MATERIAL CO., LTD. (苏州霓佳斯密封材料有限公司) SHANGHAI XINGSHENG GASKET CO., LTD. (上海兴感密封垫有限公司) SHANGHAI GOYU AUTO PARTS CO., LTD. (上海五友汽车零部件有限公司)

NICHIAS INDUSTRIAL PRODUCTS PRIVATE LTD.

NICHIAS AUTOPARTS EUROPE a.s.

India

Czech

<u> C</u>autions

1) The information and recommendation in this catalog are based on our present state of knowledge and given in good faith for customer guidance purpose, and no liability will be accepted in relation to the same.

2) Properties/applications shown in this catalog are typical. The products shown in this catalog shall not be used for any purpose other than prescribed application.

3) Performance data shown in this catalog are developed from in-house testing and/or field reports from customers. Failure to select the proper products could result in property damage and/or serious personal injury.

4) Performance verification under actual operating conditions is recommended even for the application shown in this catalog.

5) While the utmost care has been used in compiling this catalog, we assume no responsibility for errors. This edition cancels previous issues and contents of this catalog are subject to change without prior notice.

6) For safe handling recommendations and health related effects, refer to the safety data sheet (SDS) of each product, available on request.

7) All or any part of the content on this catalog may not be copied, duplicated, imitated, reused and reproduced without prior permission of NICHIAS Corporation.

